

## OUR PRODUCTS

### CLASS 4 CUSHION TIRE TRUCKS

3000-3500 lb. Trucks - FCG15-3G, FCG15-3L, FCG18-3G, FCG18-3L

#### Specifications

Model	FCG15-3G	FCG15-3L	FCG18-3G	FCG18-3L
Tire Type	Cushion Tires	Cushion Tires	Cushion Tires	Cushion Tires
Load Capacity	3000 lbs (1500 kg)	3000 lbs (1500 kg)	3500 lbs (1500 kg)	3500 lbs (1500 kg)
Service Weight	7500 lbs	7500 lbs	8000 lbs	8000 lbs
Free Lift	4.1 in (105 mm)	4.1 in (105 mm)	4.1 in (105 mm)	4.1 in (105 mm)
Max Fork Height*	130.0 in (3300 mm)	130.0 in (3300 mm)	130.0 in (3300 mm)	130.0 in (3300 mm)
Power Type	IC	IC	IC	IC
Fuel	Gasoline	LPG	Gasoline	LPG
Displacement				
Rated Output HP/RPM	JIS D1001 54.3 HP / 2700 r.p.m. (40.5kw /2700 r.p.m. : 55.1 PS/2700 r.p.m.)	JIS D1001 54.3 HP / 2700 r.p.m. (40.5kw /2700 r.p.m. : 55.1 PS/2700 r.p.m.)	JIS D1001 54.3 HP / 2700 r.p.m. (40.5kw /2700 r.p.m. : 55.1 PS/2700 r.p.m.)	JIS D1001 54.3 HP / 2700 r.p.m. (40.5kw /2700 r.p.m. : 55.1 PS/2700 r.p.m.)
Max Travel Speed w/ Load	10.0 mph (16.0 km/h)	10.0 mph (16.0 km/h)	10.0 mph (16.0 km/h)	10.0 mph (16.0 km/h)
Lift Speed w/ Load	126.0 fpm (640 mm/s)	126.0 fpm (640 mm/s)	126.0 fpm (640 mm/s)	126.0 fpm (640 mm/s)
Overall Length (without forks)	82.7 in (2100 mm)	82.7 in (2100 mm)	82.7 in (2100 mm)	82.7 in (2100 mm)
Overall Width	37.6 in (955 mm)	37.6 in (955 mm)	37.6 in (955 mm)	37.6 in (955 mm)
Overall Height Fork Lowered	83.1 in (2110 mm)	83.1 in (2110 mm)	83.1 in (2110 mm)	83.1 in (2110 mm)
Right Angle Stack	86.9 in (2205 mm)	86.9 in (2205 mm)	86.9 in (2205 mm)	86.9 in (2205 mm)

\*Based on 130" Standard Upright (Model VM330)