

OUR PRODUCTS

CLASS 4 CUSHION TIRE TRUCKS

4000 lb. Trucks - FCG20-3HG, FCG20-3HL

Specifications

Model	FCG20-3HG	FCG20-3HL
Tire Type	Cushion Tires	Cushion Tires
Load Capacity	4000 lbs (2000 kg)	4000 lbs (2000 kg)
Service Weight	7420 lbs	7420 lbs
Free Lift	4.3 in (110 mm)	4.3 in (110 mm)
Max Fork Height*	130.0 in (3300 mm)	130.0 in (3300 mm)
Power Type	Spark Ignition, IC	Spark Ignition, IC
Fuel	Gasoline	LPG
Displacement	151.8 cu-in (2.488 lit)	151.8 cu-in (2.488 lit)
Rated Output HP/RPM	JIS D1001 60.9 HP / 2800 r.p.m. (45.4kw /2800 r.p.m. : 61.8 PS/2800 r.p.m.)	JIS D1001 60.9 HP / 2800 r.p.m. (45.4kw /2800 r.p.m. : 61.8 PS/2800 r.p.m.)
Max Travel Speed w/ Load	10.0 mph (16.0 km/h)	10.0 mph (16.0 km/h)
Lift Speed w/ Load	120.1 fpm (610 mm/s)	120.1 fpm (610 mm/s)
Overall Length (without forks)	90.4 in (2295 mm)	90.4 in (2295 mm)
Overall Width	41.5 in (1055 mm)	41.5 in (1055 mm)
Overall Height Fork Lowered	83.1 in (2110 mm)	83.1 in (2110 mm)
Right Angle Stack	95.9 in (2435 mm)	95.9 in (2435 mm)

*Based on 130" Standard Upright (Model VM330)